


Single utility connection for buildings without basement



KRASO® Builder's Convenience Box - floor - 110

The flexible utility connection for heat pumps, local, district or geothermal heating, gas, water or electricity

- + The secure utility connection for heat pumps for buildings without basement:
 - KRASO® Builder's Convenience Box - floor - 110 for water-to-water heat-pumps and brine-water-heat pumps (probe and collector)
 - KRASO® Builder's Convenience Box - floor - 110 - SWP for air-to-water heatpump (split).
- + Flexible: also usable for configuring with local, district or geothermal piping systems, gas, water or electricity up to DN 50.
- + With water pressure tight surrounding KRASO® 4 Seal : exterior sealing of concrete: 10 bar!
- + Radon-tight!
- + Hose diameter: external 110 mm - internal 100 mm!
- + Stable installation device with foot extension for a save position and an easy installation
- + For flush-mount installation in the base plate – no tripping hazards, no wall damages! Including building period protection cover
- + Incl. empty pipe insert (25 cm, internal diameter: 100 mm) for a flexible floor construction
- + Incl. Flexible Empty Pipe System KRASO® FLS 110 (internal diameter: 100 mm): bending radius 1000 mm. Incl. hose connection 110 and end plug
- + DafStB waterproof concrete guideline: stress class 1 + 2, DIN 18533 W1.1 -E

