



KRASO® Basement Drain for KG 2000 **LG 1**

for the installation in areas without traffic and for the connection of up to 3 intake pipes, for the drainage of grey water, drainage capacity: 1.8 l/s, with water pressure tight surrounding, thermally welded **KRASO® 4 Seal**, lateral **KRASO® Drainage Bows DN 110** with **KRASO® 3 Seal**. Also available with **KRASO® Foil Flange**, oil- and bitumen resistant (d = approx. 50 cm). For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. | DafStB waterproof concrete guideline: stress class 1 + 2, with foil flange DIN 18533 W1-E

Type / Item	KRASO® Basement Drain for KG 2000 with plastic grate	KRASO® Basement Drain for KG 2000 with stainless steel grate
Drainage capacity	1.8 l/s	
Height	drain approx. 250 mm	
Insert frame	steplessly rotatable and height-adjustable from 30 - 60 mm	
Slot grate	class K3, 20 x 20 cm, plastic (black)	class K3, 20 x 20 cm, stainless steel
Connection	3 intake pipes: 2 x DN 50, 1 x DN 70, either for KG, HT or KG 2000 pipes	
KRASO® Basement Drain for KG 2000	539 €	682 €
KRASO® Basement Drain for KG 2000 with foil flange	668 €	781 €
KRASO® PU 50	22 €	

Scope of supply: KRASO® Basement Drain for KG 2000 with removable backwater stopper, integrated odour stopper, sludge trap filter and insert frame (telescopically height-adjustable from 30 to 60 mm and rotatable), two intakes DN 50, one intake DN 70, all intakes and drains either for KG, HT or KG 2000 pipes, with slot grate 20 x 20 cm made of black plastic or stainless steel, class K3 • **KRASO® Basement Drain for KG 2000 with foil flange** with removable backwater stopper, integrated odour stopper, sludge trap filter and insert frame (telescopically height-adjustable from 30 to 60 mm and rotatable), two intakes DN 50, one intake DN 70, all intakes and drains either for KG, HT or KG 2000 pipes, with slot grate 20 x 20 cm made of black plastic or stainless steel, class K3 300 kg



KRASO® Drains - Accessories **LG 1**

Type / Item	Insert frame extension	Insert frame extension
Item description	for KRASO® Basement Drain, KRASO® Yard Drain Type 12.5, height-adjustable from 46 - 130 mm, also suitable for KRASO® Yard/Parking Level Drain Type 1.5 with stainless steel grate	for KRASO® Yard/Parking Level Drain Type 1.5 ¹ , height-adjustable from min. 25 - 130 mm
KRASO® Drains - Accessories	30 €	99 €

¹ Not suitable for KRASO® Yard/Parking Level Drain Type 1.5 with stainless steel grate



KRASO® PU 50 **LG 1**

high-quality, permanently elastic and strong PU-sealant, also usable on moist surfaces, recommended for all products with **KRASO® Foil Flange**, colour black, 290 ml - cartridge for cartridge press

Type / Item	PU sealant
KRASO® PU 50	22 €

