



## KRASO® Sealing Insert Type TD-X

### The trio seal of a superior class

- + For core drillings or casings
- + 20% thicker steel plates made of non-corrosive stainless steel V2A!
- + Triple sealing with 60 mm seal made of specially developed sealing rubber!
- + Two circular pressure discs guarantee optimal pressure distribution!
- + More studs for even pressure distribution, welded-on studs instead of through bolts!
- + Torque Control Nut **KRASO® DKM**: integrated torque limiter - no torque wrench required!
- + MPA-tested: protects reliably against pressing water up to 10 bar!
- + Gas- and odour-tight – high-quality in terms of TA-Air!
- + Radon tightness IAF tested - meets the requirements for radon precautionary areas according to FHRK leaflet MB 101!
- + Tested according to FHRK test specification GE 101!
- + DafStB waterproof concrete guideline: stress class 1 + 2



### KRASO® Sealing Insert Type TD-X **LG 1**

for installation of pipes | DafStB waterproof concrete guideline: stress class 1 + 2

| Type / Item  | KRASO® Type TD-X |                   |                    |                    |                    |                    |                    |                    |                    |                    |
|--|------------------|-------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Core drilling / casing in mm<br>(from - to)                      | 80<br>(79 - 83)  | 100<br>(99 - 103) | 125<br>(124 - 128) | 150<br>(149 - 153) | 200<br>(198 - 203) | 250<br>(248 - 253) | 300<br>(298 - 303) | 350<br>(348 - 353) | 400<br>(398 - 403) | 500<br>(497 - 503) |
| max. external diameter<br>pipe or cable<br>from ... to ... in mm | 0 - 55           | 0 - 75            | 0 - 100            | 0 - 125            | 0 - 175            | 0 - 225            | 0 - 275            | 0 - 325            | 0 - 375            | 0 - 475            |
| <b>KRASO® Type TD-X</b>  | <b>127 €</b>     | <b>143 €</b>      | <b>167 €</b>       | <b>200 €</b>       | <b>264 €</b>       | <b>318 €</b>       | <b>469 €</b>       | <b>589 €</b>       | <b>709 €</b>       | <b>1.004 €</b>     |

\* In some cases, allen screws must be used due to the design.

All sizes and diameters available on request! All sealing inserts available in V4A for an additional charge!